

# TUTELA CAR MATRYX Cod. 1492

## DESCRIPCIÓN

Synthetic-based multigrade lubricant for Mechanical Transmissions of cars specifically for applications in which lubricants with high thermal stability are required.

## CARACTERÍSTICAS

The particular additive technology of Tutela Car Matryx, combined with the use of synthetic bases, warrants high protection against the formation of scaling, also under especially harsh operating temperature conditions.

The result is:

- | Excellent antiwear properties for optimum protection of the mechanical parts under all lubricating conditions and longer component life.
- | Viscosity grading specifically intended to optimise gearbox handling also at low temperatures
- | Fuel economy characteristics which by attenuating internal system friction allow a reduction of fuel consumption.
- | Compatible with the materials used in seals.



Tutela Car Matryx exceeds the quality requirements of the major European Manufacturers and therefore can be used in cars of every make, type and power rating.

## CONSEJO SOBRE USO

Tutela Car Matryx passes the Quality Specifications of the Major European Manufacturers and may therefore be used in Cars of every brand, type and power rating.

## RECOMENDADO POR

Fiat, Alfa Romeo, Lancia.

## DATOS TECNICOS

SAE 75W-85, API GL 4,  
FIAT 9.55550-MZ1 CONTRACTUAL TECHNICAL REF. N°F108.F02