

# TUTELA TRANSMISSION TECHNYX Cod. 1474

## DESCRIPTION

Synthetic-based multigrade lubricant for Mechanical Transmissions of cars to be used in gearbox-differential units, also fitted with hypoid gear pair and central differential (PTU).

## CHARACTERISTICS

- | Special E.P./antiwear additives to warrant optimum protection of the transmission components also under limit lubricating conditions (when moving off, at pickup torque, etc.) and with high load at low rpm.
- | Particularly suitable for gearboxes with 4-wheel drive.
- | Outstanding adhesion of the lubricating film to warrant optimum protection of the mechanical parts under all lubricating conditions which prevents gearbox noise.
- | Viscosity grading specifically intended to optimise gearbox handling under all operating temperature conditions.
- | Fuel economy product as it reduces the frictions involved with high friction control under all circumstances, thereby reducing fuel consumption.
- | Fully synthetic formula that guarantees excellent temperature-oxidation resistance properties.
- | Compatible with the materials used in seals.



TUTELA CAR TECHNYX passes the Quality Specifications of the Major European Manufacturers and may therefore be used in Cars of every brand, type and power rating.

## ADVICE ON USE

Tutela Car Technyx is grade SAE 75W-85 for use all year round. Replacement according to the manufacturer's instructions.

## RECOMMENDED BY

Fiat, Lancia, Alfa Romeo.

## TECHNICAL DATA

SAE 75W-85, API GL 4 PLUS,  
FIAT 9.55550-MX3 CONTRACTUAL TECHNICAL REF. N°F010.B05